

# REMO ONE® WHITE

distributed by



REMO ONE® is a removable foam tape made to remove cleanly from most hard non-delaminating surfaces even after extended periods of time. REMO ONE® has a permanent adhesive on one side and a removable adhesive on the other side.

Product Information		Description		
Foam:		Cross-linked Polyethylene		Thickness (inch): .032
Adhesive:		Permanent Rubber Based DRP75		
		Removable Rubber Based DRP125		
Release Liner:		63# Bleached Kraft		
Application Temperature (°F):		65 to 100		
Service Temperature (°F):		-20 to 150		
Foam		Typical Properties		Test Method
Density (lb/ft. <sup>3</sup> ):		4.5 – 5.5		ASTM D 3575
Compression Deflection (psi):	25%	4.9 min		ASTM D3575
Compression Set (%):	50%	8.6 max		ASTM D3575
Tensile Strength (psi):	MD	148 min		ASTM D3575
Elongation (% to break):	MD	166 min		ASTM D3575
Tear Resistance (lb/in):	MD	20 min		ASTM D3575
Adhesive*		Typical Properties		Test Method
		<u>DRP75</u>	<u>DRP125</u>	
180° Peel Adhesion (lb/in):		8.0 min	2.5 min	PSTC-101
Shear Resistance (hrs):				
1in <sup>2</sup> , 72°F	10 lb load:	72.0 min	100.0 min	PSTC-107
Quick Stick (lb/in):		9.0 min	2.0 min	PSTC-5
MD = Machine Direction		CD = Cross Direction		
* Tests are performed on 2 mil PET				