



K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product information

Product Name : K-Resin® KR03 Styrene-Butadiene Copolymer
 Material : 1116152, 1075489, 1076903, 1096097, 1034065, 1034224,
 1034225, 1020947, 1017035, 1021138, 1021139, 1021140,
 1021141, 1020942, 1020943, 1020944, 1020945, 1020946,
 1021137, 1020948, 1020733, 1021333, 1021334, 1021335,
 1021336, 1021337, 1021338, 1021339

EC-No.Registration number

Chemical Name	CAS-No. EC-No. Index No.	Legal Entity Registration number
Styrene	100-42-5 202-851-5 601-026-00-0	Chevron Phillips Chemicals International NV 01-2119457861-32-0005
1,3-Butadiene	106-99-0 203-450-8 601-013-00-X	Chevron Phillips Chemicals International NV 01-2119471988-16-0004
Microcrystalline/Paraffin Wax	63231-60-7 264-038-1	01-2119495561-32-XXXX

Company : Chevron Phillips Chemical Company LP
 K-Resin® SBC
 10001 Six Pines Drive
 The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
 Brusselsesteenweg 355
 B-3090 Overijse
 Belgium

SDS Requests: (800) 852-5530
 Technical Information: (832) 813-4862
 Responsible Party: Product Safety Group
 Email:sds@cpchem.com

Emergency telephone:

Health:
 866.442.9628 (North America)
 1.832.813.4984 (International)
Transport:

K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

North America: CHEMTREC 800.424.9300 or 703.527.3887
 Asia: +800 CHEMCALL (+800 2436 2255) China:+86-21-22157316
 EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
 South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Responsible Department : Product Safety and Toxicology Group
 E-mail address : SDS@CPChem.com
 Website : www.CPChem.com

The manufacturer does not recommend using any K-Resin® SBC grade in medical applications that involve permanent or temporary implantation in the human body.

SECTION 2: Hazards identification**Classification of the substance or mixture**

Regulation (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures, Annex VI, Table 3.1

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

Classification (67/548/EEC, 1999/45/EC)

In accordance with Directive 1999/45/EC, the product does not need to be classified nor labeled.
 Not a hazardous substance or mixture according to EC-directives 67/548/EEC or 1999/45/EC.

Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

SECTION 3: Composition/information on ingredients

Synonyms : Pelletized Plastic

Mixtures**Hazardous ingredients**

Chemical Name	CAS-No. EC-No. Index No.	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
Styrene-Butadiene Copolymer	9003-55-8			99

Contains no hazardous ingredients according to GHS. :

SECTION 4: First aid measures

If inhaled : Move to fresh air in case of accidental inhalation of dust or fumes from overheating or combustion. If symptoms persist, call a physician.

K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

- In case of skin contact : If the molten material gets on skin, quickly cool in water. Seek immediate medical attention. Do not try to peel the solidified material from the skin or use solvents or thinners to dissolve it.
- In case of eye contact : In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- If swallowed : Do not induce vomiting without medical advice.

SECTION 5: Firefighting measures

- Flash point : No data available
- Autoignition temperature : No data available
- Suitable extinguishing media : Water. Water mist. Dry chemical. Carbon dioxide (CO₂). Foam. If possible, water should be applied as a spray from a fogging nozzle since this is a surface burning material. The application of high velocity water will spread the burning surface layer. Avoid the use of straight streams that may create a dust cloud and the risk of a dust explosion. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Specific hazards during fire fighting : Risks of ignition followed by flame propagation or secondary explosions can be caused by the accumulation of dust, e.g. on floors and ledges.
- Special protective equipment for fire-fighters : Use personal protective equipment. Wear self-contained breathing apparatus for firefighting if necessary.
- Further information : This material will burn although it is not easily ignited.
- Fire and explosion protection : Treat as a solid that can burn. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.
- Hazardous decomposition products : Simple Hydrocarbons. Carbon oxides.

SECTION 6: Accidental release measures

- Personal precautions : Sweep up to prevent slipping hazard. Avoid breathing dust.
- Environmental precautions : Do not contaminate surface water. Prevent product from entering drains.
- Methods for cleaning up : Clean up promptly by sweeping or vacuum.
- Additional advice : Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with

K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

compressed air).

SECTION 7: Handling and storage**Handling**

Advice on safe handling : Use good housekeeping for safe handling of the product. Keep out of water sources and sewers.

Spilled pellets and powders may create a slipping hazard.

Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary, but may not by themselves be sufficient.

Advice on protection against fire and explosion : Treat as a solid that can burn. Avoid generating dust; fine dust dispersed in air in sufficient concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Storage

Requirements for storage areas and containers : Keep in a dry place. Keep in a well-ventilated place.

Advice on common storage : Do not store together with oxidizing and self-igniting products.

SECTION 8: Exposure controls/personal protection**Engineering measures**

Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally required. If heated material generates vapor or fumes that are not adequately controlled by ventilation, wear a NIOSH approved respirator. Use the following elements for air-purifying respirators: Use a positive pressure, air-supplying respirator if there is potential for uncontrolled release, exposure levels are not known, or other circumstances where air-purifying respirators may not provide adequate protection. Dust safety masks are recommended when the dust concentration is excessive.

Eye protection : Use of safety glasses with side shields for solid handling is good industrial practice. If this material is heated, wear chemical goggles or safety glasses with side shields or a face shield. If there is potential for dust, use chemical goggles.

K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

- Skin and body protection : At ambient temperatures use of clean and protective clothing is good industrial practice. If the material is heated or molten, wear thermally insulated, heat-resistant gloves that are able to withstand the temperature of the molten product. If this material is heated, wear insulated clothing to prevent skin contact if engineering controls or work practices are not adequate.
- Protective measures : Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

SECTION 9: Physical and chemical properties**Information on basic physical and chemical properties****Appearance**

- Form : Pellets
 Physical state : Solid
 Color : Clear to hazy
 Odor : Mild to no odor
 Odor Threshold : No data available

Safety data

- Flash point : No data available
- Lower explosion limit : Not applicable
- Upper explosion limit : Not applicable
- Autoignition temperature : No data available
- Thermal decomposition : Simple Hydrocarbons Carbon oxides
- pH : Not applicable
- Melting point/freezing point : Not applicable
- Initial boiling point and boiling range : Not applicable
- Vapor pressure : Not applicable
- Relative density : Not applicable
- Density : Not applicable
- Water solubility : Negligible

K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

Partition coefficient: n-octanol/water	:	No data available
Solubility in other solvents	:	No data available
Viscosity, dynamic	:	not applicable
Viscosity, kinematic	:	Not applicable
Relative vapor density	:	Not applicable
Evaporation rate	:	Not applicable
Percent volatile	:	0,2 %

SECTION 10: Stability and reactivity

Reactivity	:	This material is considered non-reactive under normal ambient and anticipated storage and handling conditions of temperature and pressure.
Chemical stability	:	This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Possibility of hazardous reactions

Conditions to avoid	:	Avoid prolonged storage at elevated temperature.
Materials to avoid	:	Avoid contact with strong oxidizing agents.
Thermal decomposition	:	Simple Hydrocarbons, Carbon oxides
Hazardous decomposition products	:	Simple Hydrocarbons Carbon oxides

SECTION 11: Toxicological information

K-Resin® KR03 Styrene-Butadiene Copolymer
Acute oral toxicity : Presumed Not Toxic

K-Resin® KR03 Styrene-Butadiene Copolymer
Acute inhalation toxicity : Presumed Not Toxic

K-Resin® KR03 Styrene-Butadiene Copolymer
Acute dermal toxicity : Presumed Not Toxic

K-Resin® KR03 Styrene-Butadiene Copolymer
Sensitization : Did not cause sensitization on laboratory animals.

K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

SECTION 12: Ecological information**Ecotoxicity effects**

Elimination information (persistence and degradability)

Bioaccumulation : Does not bioaccumulate.

Mobility : This product is insoluble in water and has neutral buoyancy.
This product may float or sink in water.

Biodegradability : This material is not expected to be readily biodegradable.

Ecotoxicology Assessment

Additional ecological information : This material is not expected to be harmful to aquatic organisms., Fish or birds may eat pellets which may obstruct their digestive tracts.

SECTION 13: Disposal considerations

The information in this SDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

SECTION 14: Transport information

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the SDS and the bill of lading.

US DOT (UNITED STATES DEPARTMENT OF TRANSPORTATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IMO / IMDG (INTERNATIONAL MARITIME DANGEROUS GOODS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

IATA (INTERNATIONAL AIR TRANSPORT ASSOCIATION)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR

K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

TRANSPORTATION BY THIS AGENCY.

ADR (AGREEMENT ON DANGEROUS GOODS BY ROAD (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

RID (REGULATIONS CONCERNING THE INTERNATIONAL TRANSPORT OF DANGEROUS GOODS (EUROPE))

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

ADN (EUROPEAN AGREEMENT CONCERNING THE INTERNATIONAL CARRIAGE OF DANGEROUS GOODS BY INLAND WATERWAYS)

NOT REGULATED AS A HAZARDOUS MATERIAL OR DANGEROUS GOODS FOR TRANSPORTATION BY THIS AGENCY.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information**National legislation**

Major Accident Hazard Legislation : 96/82/EC Update: 2003
Directive 96/82/EC does not apply

Water contaminating class (Germany) : nwg not water endangering

Notification status

Europe REACH : On the inventory, or in compliance with the inventory
United States of America TSCA : On TSCA Inventory
Canada DSL : All components of this product are on the Canadian DSL.
Australia AICS : On the inventory, or in compliance with the inventory
New Zealand NZIoC : On the inventory, or in compliance with the inventory
Japan ENCS : On the inventory, or in compliance with the inventory
Korea KECI : On the inventory, or in compliance with the inventory
Philippines PICCS : On the inventory, or in compliance with the inventory
China IECSC : On the inventory, or in compliance with the inventory


K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

SECTION 16: Other information

NFPA Classification : Health Hazard: 0
Fire Hazard: 1
Reactivity Hazard: 0

**Further information**

Legacy SDS Number : 248900

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Key or legend to abbreviations and acronyms used in the safety data sheet			
ACGIH	American Conference of Government Industrial Hygienists	LD50	Lethal Dose 50%
AICS	Australia, Inventory of Chemical Substances	LOAEL	Lowest Observed Adverse Effect Level
DSL	Canada, Domestic Substances List	NFPA	National Fire Protection Agency
NDSL	Canada, Non-Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
CNS	Central Nervous System	NTP	National Toxicology Program
CAS	Chemical Abstract Service	NZIoC	New Zealand Inventory of Chemicals
EC50	Effective Concentration	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration 50%	NOEC	No Observed Effect Concentration
EGEST	EOSCA Generic Exposure Scenario Tool	OSHA	Occupational Safety & Health Administration
EOSCA	European Oilfield Specialty Chemicals Association	PEL	Permissible Exposure Limit
EINECS	European Inventory of Existing Chemical Substances	PICCS	Philippines Inventory of Commercial Chemical Substances
MAK	Germany Maximum Concentration Values	PRNT	Presumed Not Toxic
GHS	Globally Harmonized System	RCRA	Resource Conservation Recovery Act
>=	Greater Than or Equal To	STEL	Short-term Exposure Limit
IC50	Inhibition Concentration 50%	SARA	Superfund Amendments and Reauthorization Act.
IARC	International Agency for Research on Cancer	TLV	Threshold Limit Value
IECSC	Inventory of Existing Chemical	TWA	Time Weighted Average

K-Resin® KR03 Styrene-Butadiene Copolymer

Version 1.5

Revision Date 2015-02-07

	Substances in China		
ENCS	Japan, Inventory of Existing and New Chemical Substances	TSCA	Toxic Substance Control Act
KECI	Korea, Existing Chemical Inventory	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
<=	Less Than or Equal To	WHMIS	Workplace Hazardous Materials Information System
LC50	Lethal Concentration 50%		